User Friendly and Compact



TP 130 PTO

RELIABLE CHIPPING

DESIGNED

+

MANUFACTURED

DENMARK



For Effective Work in Green Areas

- TP 130 PTO has a strong and aggressive in feed based on the hydraulic driven feed roller
- Output is 8 mm wood chip produced in a very uniform quality
- Operated with the yellow safety bar that allows the operator to start, stop and reverse the feed roller
- The stress control system TP PILOT is recommended for tractors below 40 hp
- Adjustable foot in two positions
- Turnable discharge spout

Trust in the quality



As one of the first manufacturers of wood chippers worldwide, Linddana is offering a 3 year warranty for the complete range of TP Landscape Wood Chippers.





TP 130 PT0

Technical Data


Max. wood diameter	130 mm
Infeed opening	H x W = 130 x 220 mm
Chipping principle	Disc chipper
In feed angle	Parallel to driving direction
Feed roller	1 horizontal
Rotor disc diameter	660 mm
Rotor disc weight	82 kg
Number of blades	2
Counter steel	1 horizontal and 1 vertical
Chip length	8 mm
Effect need minmax.	25 - 60 hp (18 - 45 kW)
PTO rotations per minute	540 rpm
Capacity	Up to 10 m³/hour
Weight	516 kg
Dimensions H x W x L	2207/2362 x 1217 x 2136 mm




TP 130 PTO can also easily chip thin and soft branches - due to the short distance from the feed rollers to the blades and the position of both vertical and horizontal counter steel.



A TP SERVICEBOX is included when purchasing a TP 130 PTO. The box contains an extra set of critical wear parts such as blades and counter steel.





Linddana A/S

T +45 75 80 52 00 tp@linddana.com www.linddana.com

