

Hydraulic Crawler Drill

FOX Series



 **WOLF**[®]
Excellence and Tradition in Rock Drilling

FOX Series

The Hydraulic Crawler Drill FOX Series are an excellent option for rock drilling, can be applied in Quarries, Open Cast Mining, Drilling Service Contractors and other. These equipment guarantee high productivity with low maintenance cost.

One of the main advantage the equipment is simple and very low electronic.



Carousel Rod Changer



Hose Reel



**Dust Collector
(primary and secondary)**



Slide Hood



**Extension Boom
+1.2m (3' 11")
Optional**



Grease Pump

FOX Series



**Digital Angle Inclinometer
(Optional)**



Track Frame Oscillation



**Spotlights and Windshield
Wiper**



**Cab with Air
Conditioner**



Feed Motor



Cabin Controls



**Water Cooled
Diesel Engine**

Drifter (Top Hammer)

Our top hammer is manufacture by prime components consider very simple, as Low Maintenance and High Performance.



Model	MW-80h
<i>Impact Power</i>	19 kw (26hp)
<i>Working Pressure</i>	140 bar (2.030 psi)
<i>Rotation Torque</i>	750 Nm (553 lbf/ft)
<i>Rotation Speed</i>	0 – 150 RPM
<i>Weight</i>	237 kg (522 lb)

Technical Features



Technical Features

Hole Range	<i>Rod Type</i>	T38 MF / T45 MF
	<i>Hole Depth</i>	29m (95')
	<i>Drilling Diameter</i>	2"1/2 - 4" (64 – 102 mm)
	<i>Rod Length</i>	3,6m (12')
	<i>Feed Force</i>	20 kN (4500 lbf)
Diesel Engine	<i>Brand</i>	Cummins
	<i>Model</i>	6CTA-8.3
	<i>Power</i>	214hp (158kw)
	<i>Refrigeration</i>	Water
	<i>Tank Capacity</i>	285 lt (62,9gal)
Air Compressor	<i>Compressor Type</i>	Screw
	<i>Working Pressure</i>	8 Bar (116 psi)
	<i>FAD</i>	250 pcm / cfm (7m ³ /min)
Tramming Features	<i>Tramming Speed (low)</i>	0 – 2,5 km/h (0 – 3,75 mph)
	<i>Tramming Speed (high)</i>	0 – 4,5 km/h (0 – 6,75 mph)
	<i>Traction Force</i>	7.700 N.m
	<i>Track Gradient</i>	47%
	<i>Track Frame Oscilation</i>	+/- 18°
Rod Changer	<i>Number of Rods</i>	6 + 1
	<i>Type</i>	Carousel

Dimensions	FOX 12-20	FOX 12-30
Weight	12,000 kg (26,455 lb)	13,000 kg (28,660 lb)
Width	2,500 mm (98 in.)	2,500 mm (98 in.)
Length	10,500 mm (413 in.)	10,500 mm (413 in.)
Height	3,600 mm (142 in.)	3,600 mm (142 in.)

Dimensions





www.wolfdrill.com

HEADQUARTER United States

WOLF Americas

@ info@wolfdrill.com

☎ +1 407 704 - 2051

FACTORY BRAZIL

Brazil / Indaiatuba-SP

@ info@wolf.com.br

☎ +55 (19) 3825 6530

FÝD= K7 TEMSİLCİSİ



DEMPO DIŐ TİCARET
LTD.ŐTİ.
Aksinne Mahallesi Karagöz Sk.
No:11/501
Meram / KONYA
Tel : 0332 351 01 44
dempo@dempgroup.com
www.dempogroup.com