

Flail Mulchers 20-120 HP





SMWA slim

5 40-90 HP Ø max. 5 cm [2 inch]

Ultra slim mulching mower - for use in rows with low canopy

The innovative drive concept and compact design make the SMWA slim highly manuverable in tight situations.

It allows the machine to mulch very close to the crop and therefore can work directly under the canopy without damaging fruit.

Standard version and characteristics

- > Mulches grass and brush up to 5 cm [2"]Ø
- > Working speed 3-10 km/h
- > 3 point linkage cat. 1&2 reversible
- > Linear hydraulic side shift 27 cm [10.6"]
- > 540 rpm gearbox with freewheel and through shaft
- Belt transmission with 2+3 high power belts
- Adjustable rear hood with rubber protection
- > Front protection with metal flaps
- > Support roller 152 mm Ø
- > Standard rotor with SMW flails

Optional configuration and accessories

- > 1000 rpm gearbox
- > Gearbox with automatic inverter and double freewheel
- > Additional 3-point linkage
- > Front attachment
- > Hood with rakes
- Front protection with chains instead of metal flaps
- > Roller scraper
- Attachments for undercanopy maintenance (details see separate brochure)



YouTube www.youtube.com/seppimulcher

Tools



Specifications • SMWA slim							
Working width	cm [inch]	135 [53]	145 [57]	155 [61]	175 [69]	200 [79]	225 [89]
Overall width	cm [inch]	143 [56]	153 [60]	163 [64]	183 [72]	208 [82]	233 [92]
Depth	cm [inch]	90 [35]	90 [35]	90 [35]	90 [35]	90 [35]	90 [35]
Height · top edge belt chassis	cm [inch]	54 [21]	54 [21]	54 [21]	54 [21]	54 [21]	54 [21]
Height · top edge 3 point linkage	kg [lb]	110 [43]	110 [43]	110 [43]	110 [43]	110 [43]	110 [43]
Weight (base value)	qty	460 [1,010]	470 [1,032]	495 [1,090]	520 [1,140]	550 [1,210]	600 [1,330]
Belts	qty	5	5	5	5	5	5
Flails	qty	12	15	15	18	21	24
Nominal tractor power	HP	40-90	40-90	40-90	40-90	40-90	40-90

Flail Mulchers

SMWA slim · features

Robust reinforced double wall chassis made of high tensile steel S420.



