

WOOD SPLITTER SPACCALEGNA

SPV1 PLUS - SPV2 PLUS
SPV3 PLUS



WOOD SPLITTER







OMEF-GROUP® WOOD SPLITTER is the right tool to split big logs - quickly, safely and efficiently. The cone comes with thread two or four principles, that allows an unrivalled performance on any type of wood. Equipped with an hydraulic gear motor, OMEF splitter can be also equipped with stump planer, to remove stumps from the ground, or with auger drill as well.

SPACCALEGNA

SPACCALEGNA OMEF-GROUP® permette di spaccare e sezionare tronchi di piccole e grandi dimensioni, ottimizzando e velocizzando le successive operazioni di carico, cippatura e triturazione. La macchina è disponibile con punta a vite conica a 2 o 4 principi, per rompere in più parti il legno pretagliato. In alternativa, è applicabile con punta fresa ceppi, per eliminare ceppi da strade, parcheggi, parchi e boschi, oppure con punta trivella di varie dimensioni in base al diametro di perforazione richiesto.

TECHNICAL INFORMATION

CARATTERISTICHE TECNICHE

	SPV1 PLUS		SPV2 PLUS				SPV3 PLUS
	110	210	110	210	510	810	
	1,5 - 3,5 tons	3,5 - 5 tons	1,5 - 3,5 tons	3,5 - 5 tons	5,5 - 8 tons	8 - 14 tons	14-25 tons
	100 kg 220 lbs	110 kg 240 lbs	105 kg 230 lbs	150 kg 330 lbs	285 kg 630 lbs	497 kg 1100 lbs	770 kg 1700 lbs
RPM	50 - 70	50 - 70	50 - 70	50 - 70	50 - 70	50 - 70	80 - 100
	150 - 180 bar 2175 - 2610 psi	150 - 250 bar 2175 - 3625 psi	150 - 180 bar 2175 - 2610 psi	150 - 250 bar 2175 - 3625 psi	180 - 250 bar 2610 - 3625 psi	180 - 250 bar 2610 - 3625 psi	200 - 250 bar 2900 - 3625 psi
	30 - 60 l/min 8 - 15 gpm	40 - 60 l/min 10 - 15 gpm	30 - 60 l/min 8 - 15 gpm	40 - 60 l/min 10 - 15 gpm	60 - 75 l/min 15 - 20 gpm	100 - 200 l/min 26 - 53 gpm	150 - 200 l/min 40 - 53 gpm
	1520 Nm (i = 1:4) 1120 ft lbf	2480 Nm (i = 1:4) 1830 ft lbf	1520 Nm (i = 1:4) 1120 ft lbf	2480 Nm (i = 1:4) 1830 ft lbf	6440 Nm (i = 1:4) 4750 ft lbf	11560 Nm (i = 1:4) 8530 ft lbf	20000 Nm (i=1:4) 14750 lbf
	50 mm	50 mm	50 mm	50 mm	70 mm	100 mm	Flangiato Flanged connection

OPTIONAL ACCESSORIES

ACCESSORI OPZIONALI



STUMP PLANER / FRESACEPPI:
250mm / 350mm / 500mm



AUGER DRILL / TRIVELLA:
100 mm / 200mm / 300mm / 400mm / 500mm



**4 PRINCIPLES CONE / PUNTA A VITE
CONICA 4 PRINCIPI:**
200mm / 250mm / 300mm / 400mm



**2 PRINCIPLES CONE / PUNTA A VITE
CONICA 2 PRINCIPI:**
170mm